



Edge-AI for Real-time Identification of Invasive Plant Species: On-device Machine Learning Architectures, Sensor Integration, and Low-latency Analytics for Rapid Detection, Monitoring, and Ecosystem Management in Agricultural and Natural Landscapes

Yeni Herdiyeni¹, Nabilah Khrisna Wahyuni^{2*}

¹⁻² Department of Computer Science, Faculty of Mathematics and Natural Sciences, IPB University, Bogor, Indonesia

* Corresponding Author: **Nabilah Khrisna Wahyuni**

Article Info

P-ISSN: 3051-3421

E-ISSN: 3051-343X

Volume: 02

Issue: 01

Received: 06-04-2021

Accepted: 08-05-2021

Published: 10-06-2021

Page No: 45-52

Abstract

Invasive plant species pose severe ecological and economic threats to agricultural productivity, biodiversity, and ecosystem stability worldwide, necessitating rapid and accurate detection methodologies for timely intervention. Traditional monitoring approaches, including manual surveys and laboratory-based identification, are labor-intensive, time-consuming, and impractical for large-scale or remote ecosystems. Edge artificial intelligence (Edge-AI) represents a transformative paradigm that enables real-time, on-device machine learning inference directly at the point of data acquisition, eliminating cloud dependency and enabling immediate decision-making in field conditions. This review examines the integration of edge computing platforms, embedded machine learning models, and multi-sensor imaging technologies for autonomous identification of invasive plant species in diverse ecological and agricultural settings. We discuss critical aspects of on-device model deployment, including lightweight convolutional neural networks, model quantization, feature extraction optimization, and inference acceleration techniques tailored for resource-constrained hardware. Applications spanning precision agriculture, ecological restoration, protected area management, and rapid response systems are evaluated alongside performance metrics, validation strategies, and real-world deployment case studies. The review concludes by addressing fundamental challenges including hardware limitations, environmental variability, model generalization, energy constraints, and scalability barriers, while highlighting future opportunities for integrating Edge-AI systems with unmanned aerial vehicles, Internet of Things ecosystems, and automated management platforms to achieve comprehensive, cost-effective invasive species surveillance and control.

Keywords: Edge artificial intelligence; invasive plant species; on-device machine learning; real-time detection; precision agriculture; ecosystem monitoring

1. Introduction

1.1 Ecological and Agricultural Impact of Invasive Plant Species

Invasive plant species represent one of the most significant threats to global biodiversity, ecosystem function, and agricultural productivity. These non-native plants, introduced intentionally or accidentally into new environments, exhibit aggressive growth patterns, competitive advantages over indigenous flora, and the capacity to alter fundamental ecosystem processes including nutrient cycling, hydrology, and fire regimes^[1,2]. The economic burden of invasive species exceeds billions of dollars annually, encompassing agricultural yield losses, increased management costs, reduced land values, and expenditures associated with control and eradication programs^[3]. In agricultural landscapes, invasive weeds compete with crops for essential resources including water, nutrients, and sunlight, resulting in substantial yield reductions and necessitating intensive herbicide

applications that raise environmental and health concerns ^[4]. Beyond agricultural systems, invasive plants threaten native biodiversity by displacing indigenous species, degrading wildlife habitats, and disrupting pollination networks and trophic interactions ^[5].

The capacity for early detection and rapid response represents a critical determinant of successful invasive species management, as control efficacy decreases exponentially with invasion extent and establishment duration ^[6]. However, the spatial scales of contemporary landscapes, coupled with the dynamic nature of biological invasions, present formidable challenges to conventional monitoring methodologies ^[7].

1.2 Limitations of Conventional Monitoring Methods

Traditional invasive plant species monitoring relies predominantly on field surveys conducted by trained botanists or land managers, involving visual identification, manual mapping, and periodic reassessment of known infestation sites ^[8]. While these approaches provide taxonomic accuracy, they suffer from severe limitations in spatial coverage, temporal resolution, labor requirements, and associated costs. Manual surveys are inherently subjective, with detection probability varying according to surveyor expertise, seasonal phenology, vegetation density, and accessibility constraints ^[9]. Furthermore, conventional methods typically identify established invasions rather than incipient populations, missing the critical early-detection window when eradication remains feasible and cost-effective ^[10].

Remote sensing technologies, including satellite imagery and aerial photography, have expanded spatial coverage but introduce latency between data acquisition, processing, and actionable intelligence ^[11]. Cloud-based analysis pipelines require data transmission, impose computational delays, and may encounter connectivity limitations in remote field locations where invasive species monitoring is most urgently needed ^[12]. Additionally, many invasive plant species exhibit subtle morphological or spectral signatures that challenge differentiation from native vegetation without high-resolution, ground-level observation ^[13].

1.3 Scope and Objectives of the Article

This review synthesizes recent advances in Edge-AI technologies for real-time invasive plant species identification, focusing on on-device machine learning architectures, sensor integration strategies, and field deployment frameworks. We examine hardware platforms, embedded neural network models, optimization techniques for resource-constrained environments, and applications across agricultural and ecological management contexts. The objectives are to: (1) characterize Edge-AI system architectures and their suitability for invasive species detection; (2) evaluate machine learning model deployment strategies for real-time inference; (3) assess field validation methodologies and performance benchmarks; (4) analyze operational applications in ecosystem and agricultural management; and (5) identify critical challenges and future research directions for scalable, cost-effective invasive plant monitoring systems.

2. Edge-AI Technologies for Plant Identification

2.1 On-device Machine Learning Models

Edge-AI fundamentally transforms the computational

paradigm by executing machine learning inference directly on embedded devices at the network edge, eliminating dependence on cloud infrastructure and enabling real-time, autonomous decision-making in field environments ^[14]. For invasive plant identification, on-device models must achieve high classification accuracy while operating within stringent constraints of memory, processing power, and energy consumption characteristic of portable and battery-powered platforms ^[15].

Lightweight convolutional neural networks (CNNs) represent the predominant architecture for edge-based image classification tasks. Models such as MobileNet, SqueezeNet, and EfficientNet employ depth-wise separable convolutions, architectural optimization, and compound scaling strategies to minimize computational complexity while preserving discriminative capacity ^[16, 17]. These networks typically achieve inference latencies measured in milliseconds on embedded processors, enabling real-time video stream analysis crucial for mobile monitoring applications ^[18]. Transfer learning approaches, wherein models pre-trained on large-scale datasets are fine-tuned for specific invasive species, dramatically reduce training data requirements and accelerate deployment timelines ^[19].

Model quantization techniques convert floating-point weights and activations to lower-precision representations, typically 8-bit integers, reducing memory footprint by approximately 75% and accelerating inference through optimized integer arithmetic operations ^[20]. Knowledge distillation further compresses models by training compact student networks to replicate the behavior of larger teacher models, maintaining accuracy while achieving substantial size reductions ^[21]. Hardware-aware neural architecture search automates model design by optimizing architectures specifically for target edge devices, balancing accuracy against latency and energy consumption ^[22].

2.2 Sensors and Imaging Modalities for Invasive Plant Detection

Effective invasive plant identification requires imaging sensors capable of capturing discriminative spectral, spatial, and temporal features under diverse field conditions. RGB cameras provide the foundation for visual pattern recognition, enabling identification based on leaf morphology, growth habit, flowering characteristics, and canopy structure ^[23]. High-resolution cameras integrated with edge processors facilitate detailed texture analysis and fine-scale phenotypic differentiation essential for distinguishing morphologically similar species ^[24].

Multispectral and hyperspectral imaging extends detection capabilities by capturing reflectance across narrow wavelength bands spanning visible, near-infrared, and shortwave infrared regions ^[25]. Invasive species often exhibit distinctive spectral signatures arising from differences in leaf chemistry, pigment composition, water content, and cellular structure compared to native vegetation ^[26]. Edge-compatible multispectral cameras, typically acquiring 4-12 spectral bands, balance discriminative power against data volume and processing requirements ^[27]. Integration of normalized difference vegetation index (NDVI) and other vegetation indices enhances detection of stressed or phenologically distinct invasive plants ^[28].

Thermal infrared sensors detect temperature variations associated with differential transpiration rates, canopy structure, or metabolic activity, providing complementary

information particularly valuable for distinguishing invasive species during dormant periods when visual differences diminish [29]. LiDAR (Light Detection and Ranging) sensors capture three-dimensional canopy structure, enabling

identification based on plant height, volume, and architectural characteristics [30]. Table 1 summarizes principal hardware platforms, sensors, and imaging technologies deployed in Edge-AI systems for invasive plant detection.

Table 1: Edge-AI Hardware Platforms, Sensors, and Imaging Technologies for Plant Detection

Platform Type	Representative Devices	Sensor Modalities	Processing Capabilities	Typical Applications
Embedded AI Accelerators	NVIDIA Jetson (Nano, Xavier), Google Coral Edge TPU, Intel Neural Compute Stick	RGB cameras, multispectral imagers	GPU/TPU acceleration, 0.5-32 TOPS	Stationary monitoring stations, mobile ground platforms
Smartphone/Tablet	Commercial Android/iOS devices with integrated AI chips	RGB cameras, depth sensors	1-5 TOPS, optimized neural engines	Citizen science, rapid field surveys, extension services
Microcontroller Units	Arduino Portenta, ESP32-CAM, STM32 with TensorFlow Lite	Low-resolution cameras, environmental sensors	0.1-1 TOPS, ultra-low power	Distributed sensor networks, long-term remote monitoring
UAV-integrated Systems	DJI Manifold, custom drone payloads	RGB, multispectral, thermal, LiDAR	Variable, mission-dependent	Aerial surveys, inaccessible terrain, rapid area coverage
Agricultural Robotics	Autonomous rovers, weed-detection robots	High-resolution RGB, multispectral, stereo vision	5-20 TOPS, ruggedized platforms	Precision agriculture, targeted herbicide application

2.3 Edge Computing Infrastructure and Low-latency Analytics

Edge computing architecture distributes computational resources across hierarchical tiers, positioning intelligence at the data source to minimize latency, reduce bandwidth consumption, and enable autonomous operation during network disruptions [31]. For invasive plant monitoring, edge infrastructure typically comprises field-deployed devices executing immediate inference, intermediate fog nodes aggregating data from multiple sensors, and optional cloud backends providing long-term storage, model updates, and comprehensive analytics [32].

Real-time requirements for invasive species detection—particularly in applications involving autonomous intervention or human safety considerations—necessitate inference latencies below 100 milliseconds to support immediate decision-making [33]. Hardware accelerators

including Graphics Processing Units (GPUs), Tensor Processing Units (TPUs), and Field Programmable Gate Arrays (FPGAs) achieve this performance through parallel computation and specialized neural network operations. Power efficiency remains critical for battery-operated field devices, with modern edge AI accelerators achieving inference energy consumption in the millijoule range per image, enabling extended autonomous deployment. Data preprocessing at the edge reduces transmission requirements by filtering irrelevant information and transmitting only classified detections or alerts rather than raw imagery. This approach conserves energy, reduces network load, and addresses privacy concerns in collaborative monitoring initiatives. Edge devices implement adaptive sampling strategies, increasing image acquisition frequency when invasive species are detected and entering low-power standby modes during periods of inactivity.




Fig 1: Hierarchical Edge-AI Architecture for Real-time Invasive Plant Monitoring

3. Real-time Detection and Classification

3.1 Data Preprocessing and Feature Extraction

Effective real-time invasive plant identification requires robust preprocessing pipelines that accommodate variable illumination, viewing angles, occlusions, and environmental conditions encountered in field deployments. Image normalization techniques standardize pixel intensity distributions, mitigating effects of changing light conditions across times of day and weather patterns. Geometric transformations including rotation, scaling, and perspective correction compensate for camera orientation variability in handheld or mobile platforms.

Background segmentation isolates target vegetation from soil, water, infrastructure, and other non-plant elements, focusing computational resources on relevant image regions and improving classification accuracy. Classical computer vision techniques such as color-based thresholding, edge detection, and region growing provide computationally efficient segmentation suitable for edge devices. Semantic segmentation networks, when appropriately optimized, achieve superior accuracy by learning complex decision boundaries directly from training data.

Feature extraction transforms raw imagery into discriminative representations emphasizing characteristics relevant for species differentiation. Traditional approaches extract hand-crafted features including texture descriptors (Local Binary Patterns, Gabor filters), shape metrics (leaf area, perimeter complexity, aspect ratio), and color histograms. Deep learning architectures automatically learn hierarchical features through successive convolutional layers, capturing low-level edges and textures progressing to high-level semantic patterns and species-specific signatures. Feature pyramid networks extract multi-scale representations, enabling detection of invasive plants across

varying sizes and distances from the sensor.

3.2 Model Deployment and Inference Optimization

Deploying machine learning models to resource-constrained edge devices requires specialized software frameworks and optimization strategies that balance accuracy against computational efficiency. TensorFlow Lite, PyTorch Mobile, and ONNX Runtime provide cross-platform inference engines supporting quantized models, hardware acceleration, and memory-efficient execution. These frameworks implement graph optimization techniques including operator fusion, constant folding, and dead code elimination that reduce model complexity without affecting outputs.

Runtime optimization encompasses dynamic batch sizing, where multiple images are processed simultaneously when temporal constraints permit, amortizing overhead costs across samples. Pruning removes redundant network parameters, creating sparse models with reduced memory footprint and accelerated inference, particularly when combined with specialized sparse computation kernels. Early exit strategies incorporate intermediate classifiers within deep networks, terminating inference when confidence thresholds are exceeded, thereby reducing average computation for easily classified samples.

Hardware-software co-design optimizes model architectures specifically for target processors, exploiting instruction set features, cache hierarchies, and parallelization capabilities. For invasive plant detection deployed on agricultural robots or unmanned aerial vehicles, inference scheduling coordinates model execution with vehicle motion, sensor triggering, and intervention systems to maximize coverage efficiency. Figure 2 illustrates the complete workflow from image acquisition through preprocessing, feature extraction, and optimized inference on edge devices.




Fig 2: Workflow of On-device Image Acquisition, Preprocessing, and Machine Learning Inference

3.3 Field Validation and Performance Metrics

Rigorous field validation under operational conditions is essential for establishing Edge-AI system reliability and informing deployment decisions. Validation protocols assess model performance across representative environmental conditions, phenological stages, vegetation densities, and lighting scenarios encountered during actual monitoring operations. Hold-out test sets comprising images from geographic locations, seasons, and sensor configurations distinct from training data evaluate model generalization capacity.

Classification accuracy metrics including precision (positive predictive value), recall (sensitivity), and F1-score quantify detection performance, with recall particularly critical for invasive species monitoring where false negatives represent missed early-detection opportunities. Confusion matrices identify systematic misclassification patterns, revealing morphologically similar species pairs requiring enhanced training data or alternative discriminative features. Receiver operating characteristic curves and area under curve metrics assess performance across varying confidence thresholds, enabling operators to tune systems according to management priorities.

Real-time performance benchmarks measure inference latency, throughput (images processed per second), and energy consumption under representative workloads. These metrics inform deployment feasibility for specific hardware platforms and use cases. Localization accuracy evaluates spatial precision of invasive species detections, critical for generating actionable maps and guiding targeted interventions. Long-term field trials assess system reliability, failure modes, environmental durability, and maintenance requirements across extended deployment periods.

4. Applications in Ecosystem and Agricultural Management

4.1 Rapid Mapping and Monitoring of Invasive Species

Edge-AI enables comprehensive spatial mapping of invasive plant distributions at unprecedented temporal resolution and geographic scale. Mobile platforms including all-terrain vehicles, autonomous robots, and handheld devices equipped with edge processors generate real-time invasive species maps during field traverses, eliminating post-processing delays associated with conventional remote sensing workflows. Continuous monitoring networks comprising distributed edge devices detect new invasions within hours or days of establishment, vastly improving early-detection capabilities compared to annual or seasonal manual surveys. Unmanned aerial vehicles (UAVs) equipped with lightweight edge processors and multispectral cameras conduct aerial surveys at spatial resolutions unattainable from satellites while providing immediate onboard processing and detection. Edge-based aerial monitoring proves particularly valuable for surveying inaccessible terrain, large protected areas, or post-disturbance landscapes where rapid invasive species colonization threatens ecosystem recovery. Integration with Geographic Information Systems enables automated updating of invasive species databases, tracking invasion dynamics, and assessing control program effectiveness.

Citizen science initiatives leverage smartphone-based Edge-AI applications that enable non-specialist volunteers to contribute validated invasive species observations, dramatically expanding monitoring capacity. On-device models provide immediate identification feedback, improving data quality by flagging uncertain classifications for expert review while automatically accepting high-confidence detections. Figure 3 depicts representative field deployment scenarios for Edge-AI invasive plant monitoring systems.




Fig 3: Field Deployment of Edge-AI Devices for Rapid Invasive Plant Monitoring in Agricultural or Natural Ecosystems

4.2 Early Intervention and Management Strategies

Real-time invasive species detection enables immediate management responses that maximize control efficacy while minimizing costs and environmental impacts. Precision agriculture systems integrate edge-based detection with automated spray systems, delivering herbicides exclusively to invasive weed locations rather than broadcast applications, reducing chemical usage by 70-90% while maintaining equivalent control. Spot treatment guided by Edge-AI detection proves especially valuable for managing herbicide-resistant invasive species or operating in environmentally sensitive areas where minimizing chemical inputs is paramount.

Early-detection rapid-response (EDRR) programs utilize Edge-AI monitoring to identify incipient invasions when populations remain small, localized, and amenable to eradication. Real-time alerts trigger immediate field verification and control actions within optimal intervention windows, dramatically improving eradication success rates compared to delayed responses following traditional detection. Economic analyses demonstrate that EDRR programs leveraging Edge-AI detection generate benefit-cost ratios exceeding 10:1 through avoided future control expenditures and ecosystem damages.

Adaptive management frameworks incorporate Edge-AI monitoring data into decision-support systems that optimize resource allocation across multiple invasive species and management units. Spatial prioritization algorithms identify high-value conservation areas or agricultural lands where invasive species pose greatest threats, directing limited control resources for maximum impact. Temporal analysis of detection patterns informs optimal treatment timing based on phenology, weather conditions, and biological susceptibility windows.

4.3 Integration with Decision-Support Systems

Edge-AI invasive plant detection systems increasingly function as components within comprehensive environmental management platforms integrating multiple data streams, predictive models, and stakeholder interfaces. Decision-support systems combine real-time detection data with species distribution models, climate projections, land use patterns, and ecological vulnerability assessments to forecast invasion risks and evaluate alternative management scenarios. Visualization interfaces present complex spatial-temporal patterns in accessible formats for land managers, policymakers, and community stakeholders.

Integration with existing agricultural management platforms enables seamless incorporation of invasive weed monitoring into precision farming workflows, variable rate application systems, and farm management information systems.

Automated reporting generates regulatory compliance documentation for herbicide applications, organic certification, or conservation program requirements. Cloud connectivity, where available, facilitates collaborative monitoring across jurisdictional boundaries, enabling coordinated regional control programs and information sharing among land management agencies.

Machine learning pipelines continuously improve model performance through active learning strategies that identify uncertain predictions for expert labeling, automatically incorporating validated field observations into expanding training datasets. Federated learning approaches enable model refinement using distributed data from multiple edge devices while preserving privacy and reducing communication overhead. These adaptive systems demonstrate progressively improving accuracy as deployment duration increases and training data accumulates.

5. Challenges and Future Perspectives

5.1 Hardware, Power, and Deployment Constraints

Despite rapid advances in edge computing capabilities, fundamental hardware limitations constrain invasive plant monitoring system performance and deployment scope. Processing power, memory capacity, and energy availability represent mutually constraining factors in mobile and remote deployments where size, weight, and cost must be minimized. Current edge AI accelerators achieve impressive inference efficiency but remain power-hungry relative to ultra-low-power microcontrollers suitable for long-term unattended deployment, necessitating strategic trade-offs between detection capability and operational duration.

Environmental durability requirements for field-deployed devices exceed consumer electronics specifications, demanding ruggedization against moisture, temperature extremes, dust, mechanical shock, and biological factors including insects and fungal growth. Solar power systems extend deployment duration but introduce dependencies on weather conditions and seasonal sunlight availability. Battery technology advances remain critical for achieving multi-year autonomous operation necessary for monitoring remote protected areas or extensive agricultural landscapes.

Cost considerations significantly impact system scalability, with high-performance edge AI platforms priced beyond feasible deployment densities for comprehensive landscape coverage. Emerging ultra-low-cost microcontroller-based solutions demonstrate promising capabilities but currently sacrifice accuracy, versatility, or real-time performance. Table 2 synthesizes advantages, limitations, and performance characteristics of contemporary Edge-AI systems for invasive plant identification.

Table 2: Advantages, Limitations, and Performance Metrics of Edge-AI Systems for Invasive Plant Species Identification

System Characteristic	Advantages	Limitations	Typical Performance Metrics
Real-time On-device Inference	Eliminates cloud latency (1-5s → <100ms); enables offline operation; immediate decision-making	Constrained model complexity; limited computational resources	Inference: 20-200ms; Accuracy: 85-95%; Power: 2-15W
Lightweight Neural Networks	Low memory footprint (5-50MB); fast inference; deployable on embedded devices	Reduced capacity vs. cloud models; potential accuracy trade-offs	Parameters: 1-10M; FLOPS: 100M-2B
Multi-sensor Fusion	Enhanced discrimination through complementary spectral/spatial data; robustness to environmental variation	Increased hardware complexity; higher power consumption; data synchronization	Accuracy improvement: 5-15%; Power: 5-25W
Autonomous Field Deployment	Continuous monitoring; early detection; reduced labor costs; scalable coverage	Environmental durability challenges; power management; maintenance requirements	Deployment duration: weeks-months; Detection probability: 70-90%
Integration with Intervention Systems	Immediate targeted control; reduced chemical usage (70-90%); precision management	System complexity; calibration requirements; operational costs	Treatment accuracy: ±10cm; Chemical reduction: 70-95%
Privacy and Data Security	Local processing preserves sensitive location data; reduced transmission vulnerability	Limited collaborative learning; isolated model updates	Data retention: device-local; Transmission: alerts only

5.2 Model Generalization and Environmental Variability

Invasive plant species exhibit substantial phenotypic plasticity in response to environmental gradients, nutrient availability, competition, and disturbance regimes, challenging development of universally applicable classification models. Seasonal phenology introduces dramatic temporal variation in morphology, coloration, and spectral signatures, with dormant or juvenile plants particularly difficult to distinguish from native vegetation. Training datasets must encompass representative samples across geographic ranges, environmental conditions, growth stages, and competitive contexts to achieve robust generalization.

Environmental factors including illumination angle and intensity, atmospheric conditions, soil backgrounds, and vegetation density confound species identification through effects on apparent color, texture, and spectral reflectance [99]. Shadows, sun glare, and variable cloud cover introduce image quality variability that degrades model performance when training data distributions fail to match deployment conditions. Domain adaptation techniques and augmentation strategies partially address these challenges but cannot fully compensate for unrepresented condition.

Morphological similarity among closely related invasive and native species represents a persistent challenge, with some taxonomic groups requiring reproductive structures, microscopic features, or molecular analysis for definitive identification. Hierarchical classification approaches identifying genus-level invasive groups provide useful coarse-grained detection when species-level discrimination proves unreliable. Uncertainty quantification methods flag low-confidence predictions for expert verification, balancing automation benefits against identification accuracy.

5.3 Scalability, Cost, and Regulatory Considerations

Scaling Edge-AI invasive plant monitoring from demonstration projects to operational landscape-scale deployments requires addressing economic, institutional, and regulatory barriers alongside technical challenges. Initial capital costs for hardware procurement, sensor networks, and infrastructure development represent substantial investments requiring cost-benefit justification through demonstrated efficacy and return on investment. Operational expenses including maintenance, data management, model updates, and expert support must remain financially sustainable

relative to management budgets and competing priorities.

Standardization of data formats, model architectures, and performance metrics would facilitate technology transfer, enable benchmarking across systems, and reduce duplication of development efforts. Open-source model repositories and pre-trained networks for common invasive species could dramatically accelerate deployment in new regions and reduce barriers to adoption. However, intellectual property considerations, competitive dynamics among technology providers, and privacy concerns complicate collaborative development.

Regulatory frameworks governing herbicide applications, data privacy, autonomous vehicle operations, and environmental monitoring currently lag technological capabilities, creating uncertainty for operational deployments. Validation protocols establishing Edge-AI system reliability for regulatory compliance purposes require development and standardization. Liability questions surrounding automated decision-making, particularly for chemical applications or interventions affecting non-target organisms, necessitate clear legal frameworks and insurance mechanisms.

Future developments integrating Edge-AI invasive plant detection with emerging technologies including 5G connectivity, advanced robotics, satellite IoT networks, and augmented reality interfaces promise transformative capabilities for ecosystem management. Continued miniaturization and energy efficiency improvements will enable deployment at unprecedented scales and durations. Critically, success depends on interdisciplinary collaboration among ecologists, computer scientists, engineers, land managers, and policymakers to ensure technical solutions address operational requirements and ecological realities.

6. Conclusion

Edge-AI represents a paradigm shift for invasive plant species monitoring, enabling real-time, autonomous detection and identification at scales and resolutions previously unattainable through conventional methodologies. Integration of lightweight machine learning models, multi-sensor imaging systems, and optimized edge computing platforms delivers immediate actionable intelligence directly in field environments, eliminating cloud dependencies and supporting rapid response to emerging invasions. The technology demonstrates particular promise for precision

agriculture applications, early-detection rapid-response programs, and continuous monitoring of high-value conservation areas where timely intervention determines management success.

Significant technical challenges persist, including hardware constraints, power limitations, model generalization across environmental variability, and costs associated with landscape-scale deployment. However, rapid advances in embedded AI accelerators, model optimization techniques, and energy-efficient computing architectures continue expanding capabilities while reducing barriers to adoption. Future trajectories emphasize integration with autonomous platforms, collaborative monitoring networks, and comprehensive decision-support systems that situate invasive species detection within holistic ecosystem management frameworks.

Realizing the transformative potential of Edge-AI for invasive plant management requires sustained investment in interdisciplinary research, development of open standards and shared resources, establishment of validation protocols and regulatory frameworks, and genuine partnerships between technology developers and end-user communities. As these elements coalesce, Edge-AI promises to fundamentally enhance humanity's capacity to detect, monitor, and control invasive plant species, thereby protecting biodiversity, safeguarding agricultural productivity, and preserving ecosystem integrity for future generations.

7. References

- Vilà M, Espinar JL, Hejda M, *et al.* Ecological impacts of invasive alien plants: a meta-analysis of their effects on species, communities and ecosystems. *Ecol Lett.* 2011;14(7):702-708.
- Pyšek P, Hulme PE, Simberloff D, *et al.* Scientists' warning on invasive alien species. *Biol Rev.* 2020;95(6):1511-1534.
- Diagne C, Leroy B, Vaissière AC, *et al.* High and rising economic costs of biological invasions worldwide. *Nature.* 2021;592(7855):571-576.
- Oerke EC. Crop losses to pests. *J Agric Sci.* 2006;144(1):31-43.
- Pimentel D, Zuniga R, Morrison D. Update on the environmental and economic costs associated with alien-invasive species in the United States. *Ecol Econ.* 2005;52(3):273-288.
- Simberloff D, Martin JL, Genovesi P, *et al.* Impacts of biological invasions: what's what and the way forward. *Trends Ecol Evol.* 2013;28(1):58-66.
- Bradley BA, Laginhas BB, Whitlock R, *et al.* Disentangling the abundance-impact relationship for invasive species. *Proc Natl Acad Sci USA.* 2019;116(20):9919-9924.
- Jarnevich CS, Stohlgren TJ, Kumar S, *et al.* Caveats for correlative species distribution modeling. *Ecol Inform.* 2015;29:6-15.
- Simpson A, Jarnevich CS, Madsen J, *et al.* Invasive species information networks: collaboration at multiple scales for prevention, rapid response, and control. *Biodiv Conserv.* 2009;18:5-24.
- Epanchin-Niell RS, Hastings A. Controlling established invaders: integrating economics and spread dynamics to determine optimal management. *Ecol Lett.* 2010;13(4):528-541.
- Bradley BA. Remote detection of invasive plants: a review of spectral, textural and phenological approaches. *Biol Invasions.* 2014;16(7):1411-1425.
- Zhou W, Peng Y, Li H. Edge intelligence: paving the last mile of artificial intelligence with edge computing. *Proc IEEE.* 2019;107(8):1738-1762.
- Andrew ME, Ustin SL. The role of environmental context in mapping invasive plants with hyperspectral image data. *Remote Sens Environ.* 2008;112(12):4301-4317.
- Shi W, Cao J, Zhang Q, *et al.* Edge computing: vision and challenges. *IEEE Internet Things J.* 2016;3(5):637-646.
- Kamilaris A, Prenafeta-Boldú FX. Deep learning in agriculture: a survey. *Comput Electron Agric.* 2018;147:70-90.
- Howard AG, Zhu M, Chen B, *et al.* MobileNets: efficient convolutional neural networks for mobile vision applications. *arXiv preprint arXiv:1704.04861.* 2017.
- Tan M, Le QV. EfficientNet: rethinking model scaling for convolutional neural networks. *Proc Int Conf Mach Learn.* 2019;97:6105-6114.
- Tang J, Chen Y, Chakrabarty K, *et al.* Real-time object detection for edge devices: a survey. *IEEE Trans Comput Aided Des Integr Circuits Syst.* 2022;41(11):3837-3869.
- Weiss K, Khoshgoftaar TM, Wang D. A survey of transfer learning. *J Big Data.* 2016;3(1):1-40.
- Jacob B, Kligys S, Chen B, *et al.* Quantization and training of neural networks for efficient integer-arithmetic-only inference. *Proc IEEE Conf Comput Vis Pattern Recognit.* 2018:2704-2713.
- Gou J, Yu B, Maybank SJ, *et al.* Knowledge distillation: a survey. *Int J Comput Vis.* 2021;129:1789-1819.
- Cai H, Zhu L, Han S. ProxylessNAS: direct neural architecture search on target task and hardware. *Proc Int Conf Learn Represent.* 2019.
- Wäldchen J, Mäder P. Machine learning for image based species identification. *Methods Ecol Evol.* 2018;9(11):2216-2225.
- dos Santos Ferreira A, Freitas DM, da Silva GG, *et al.* Weed detection in soybean crops using ConvNets. *Comput Electron Agric.* 2017;143:314-324.
- Huang H, Deng J, Lan Y, *et al.* A fully convolutional network for weed mapping of unmanned aerial vehicle (UAV) imagery. *PLoS One.* 2018;13(4):e0196302.
- Hennessy A, Clarke K, Lewis M. Hyperspectral classification of plants: a review of waveband selection generalisability. *Remote Sens.* 2020;12(1):113.
- Guo W, Rage UK, Ninomiya S. Illumination invariant segmentation of vegetation for time series wheat images based on decision tree model. *Comput Electron Agric.* 2013;96:58-66.
- Tucker CJ. Red and photographic infrared linear combinations for monitoring vegetation. *Remote Sens Environ.* 1979;8(2):127-150.
- Maes WH, Steppe K. Perspectives for remote sensing with unmanned aerial vehicles in precision agriculture. *Trends Plant Sci.* 2019;24(2):152-164.
- Deery DM, Rebetzke GJ, Jimenez-Berni JA, *et al.* Methodology for high-throughput field phenotyping of canopy temperature using airborne thermography. *Front Plant Sci.* 2016;7:1808.
- Satyanarayanan M. The emergence of edge computing. *Computer.* 2017;50(1):30-39.
- Cheng Y, Peng M, Fan Q, *et al.* Edge computing-based intelligent agriculture: opportunities and challenges. *IEEE Comput Intell Mag.* 2021;16(3):20-32.