



Smart Compost Quality Monitoring Using Hyperspectral Imaging and Machine Learning: Automated, Non-Destructive Approaches for Nutrient Characterization and Sustainable Organic Fertilizer Management

Dr. Bram T Reed ^{1*}, Dr. Claire D Petit ²

¹⁻² Department of Agricultural Engineering, University of São Paulo, Piracicaba, Brazil

* Corresponding Author: Dr. Bram T Reed

Article Info

P-ISSN: 3051-3421

E-ISSN: 3051-343X

Volume: 04

Issue: 01

Received: 17-06-2023

Accepted: 19-07-2023

Published: 21-08-2023

Page No: 66-75

Abstract

The expanding adoption of organic fertilizers in sustainable agriculture necessitates reliable and rapid quality assessment methods to ensure optimal nutrient delivery and environmental safety. Traditional laboratory-based compost characterization techniques, while accurate, are time-consuming, destructive, and limited in spatial coverage, hindering real-time process control and large-scale quality monitoring. Hyperspectral imaging (HSI) has emerged as a transformative non-destructive technology that captures both spatial and spectral information across hundreds of contiguous wavelength bands, enabling detailed characterization of compost chemical composition, maturity status, and nutrient content. When integrated with machine learning algorithms, HSI systems can automate the detection and quantification of key quality parameters including organic carbon, nitrogen, phosphorus, moisture content, and maturity indices without sample preparation or chemical reagents. This review examines the principles, applications, and computational frameworks underlying smart compost quality monitoring systems that combine hyperspectral imaging with advanced data analytics. We analyze spectral signatures associated with compost constituents, evaluate machine learning models for predictive nutrient estimation, and discuss automated classification approaches for maturity grading. The integration of these technologies offers significant advantages for precision agriculture, enabling site-specific organic fertilizer management, reducing environmental pollution from improper compost application, and supporting circular economy initiatives in agricultural waste recycling. Despite considerable progress, challenges remain in standardizing acquisition protocols, improving model transferability across different compost types, and reducing system costs for widespread adoption. Future developments in deep learning architectures, sensor miniaturization, and cloud-based decision support platforms promise to enhance the accessibility and impact of intelligent compost monitoring technologies.

Keywords: Hyperspectral imaging, Compost quality assessment, Machine learning, Organic fertilizer monitoring, Precision agriculture, Sustainable waste management, Nutrient characterization

1. Introduction

Composting represents a cornerstone of sustainable agricultural practices, converting organic wastes into valuable soil amendments that enhance soil fertility, improve water retention, and reduce dependence on synthetic fertilizers ^[1, 2]. As global agricultural systems transition toward circular economy models, the production and utilization of compost and other organic fertilizers have expanded dramatically, with worldwide organic fertilizer markets projected to exceed substantial growth in the coming decade ^[3]. However, the agronomic effectiveness and environmental safety of compost application critically depend on

its quality characteristics, including nutrient composition, maturity level, stability, and absence of phytotoxic compounds [4, 5].

Conventional compost quality assessment relies predominantly on laboratory-based analytical methods such as wet chemistry, chromatography, and spectrophotometry [6]. While these techniques provide accurate quantification of individual parameters, they suffer from several fundamental limitations: destructive sampling requirements, lengthy analysis times ranging from days to weeks, high operational costs, inability to capture spatial heterogeneity within compost batches, and limited applicability for real-time process monitoring during composting operations [7, 8]. These constraints impede the optimization of composting processes, complicate quality assurance in commercial compost production, and restrict the implementation of precision agriculture strategies that require site-specific organic fertilizer recommendations based on actual nutrient content [9].

The advent of hyperspectral imaging (HSI) technology offers transformative potential for overcoming these limitations through rapid, non-destructive, and spatially resolved characterization of compost materials [10, 11]. Hyperspectral imaging systems capture reflected or emitted electromagnetic radiation across hundreds of contiguous narrow spectral bands, typically spanning visible, near-infrared, and shortwave infrared regions (400–2500 nm) [12]. The resulting three-dimensional hyperspectral data cubes contain both spatial information about sample distribution and spectral signatures that reveal molecular composition, as different organic and inorganic constituents exhibit characteristic absorption and reflection patterns related to their chemical bonds and electronic transitions [13, 14].

When coupled with machine learning algorithms, hyperspectral imaging enables automated extraction of quality-related information from complex spectral data, facilitating rapid prediction of nutrient concentrations, classification of maturity stages, and detection of contamination or quality defects [15, 16]. Machine learning models can identify subtle spectral patterns imperceptible to conventional analysis, handle high-dimensional data structures inherent to hyperspectral imaging, and provide calibration-free or minimally calibrated predictions once adequately trained [17]. This synergy between advanced sensing technology and computational intelligence forms the foundation of smart compost quality monitoring systems that promise to revolutionize organic fertilizer management in precision agriculture [18, 19].

This article provides a comprehensive review of hyperspectral imaging and machine learning approaches for automated compost quality assessment. We examine the fundamental principles of hyperspectral sensing applied to organic materials, analyze spectral characteristics associated with key compost quality parameters, evaluate machine learning methodologies for nutrient prediction and maturity classification, and discuss practical applications in agricultural and environmental contexts. Additionally, we identify current challenges and future research directions that will shape the development and deployment of intelligent compost monitoring technologies.

2. Compost Quality Parameters and Assessment Challenges

2.1. Physical, Chemical, and Biological Indicators

Compost quality encompasses multiple interdependent physical, chemical, and biological attributes that collectively determine its suitability for agricultural application and environmental safety [20]. Physical parameters include particle size distribution, bulk density, moisture content, color, and odor characteristics, which influence handling properties, application uniformity, and decomposition rates in soil [21]. Moisture content typically ranging from 30–60% affects microbial activity during composting and determines storage stability [22].

Chemical quality indicators form the core of compost characterization, with organic matter content, total nitrogen, available phosphorus, exchangeable potassium, and carbon-to-nitrogen (C/N) ratio serving as primary parameters [23]. Organic carbon content, generally comprising 15–45% of dry matter, reflects the energy and humus-building potential of compost [24]. Nitrogen concentration, typically 1–3% on a dry basis, determines the fertilizer value and influences nutrient release patterns following soil incorporation [25]. The C/N ratio, ideally between 15 and 25 for mature compost, indicates nitrogen availability and immobilization risk [26]. Additional chemical parameters including pH (typically 6.5–8.5), electrical conductivity, heavy metal concentrations, and content of potentially phytotoxic compounds such as ammonia and volatile organic acids are critical for safety assessment [27, 28].

Biological indicators, particularly respiration rate and microbial community composition, provide information about compost stability and ongoing decomposition processes [29]. Maturity indices, including germination index, which measures phytotoxicity through seed germination tests, serve as integrative parameters that combine multiple quality aspects [30].

2.2. Compost Maturity and Stability Indices

Compost maturity refers to the degree of organic matter decomposition and the absence of phytotoxic substances, while stability indicates the resistance to further biological degradation [31]. Immature compost can cause nitrogen immobilization, oxygen depletion in soil, production of phytotoxic compounds, and introduction of pathogens, making maturity assessment essential for safe agricultural use [32]. Traditional maturity indicators include temperature decline, C/N ratio reduction, humification indices based on spectroscopic measurements, and biological assays such as the Solvita test [33]. However, no single universal maturity index exists, as optimal values vary depending on feedstock composition and intended application [34].

2.3. Variability in Raw Materials and Processes

Compost quality exhibits substantial variability arising from diverse feedstock sources including agricultural residues, food waste, animal manures, municipal biosolids, and yard trimmings [35]. Each feedstock possesses distinct initial chemical composition, degradation kinetics, and nutrient profiles. Furthermore, composting process parameters such as aeration regime, moisture management, temperature

profile, and residence time significantly influence final product characteristics^[36]. This inherent heterogeneity both within and between compost batches complicates quality prediction and necessitates frequent monitoring throughout production and storage^[37].

2.4. Limitations of Laboratory-Based Methods

Conventional analytical approaches, while providing quantitative accuracy, face multiple operational constraints^[38]. Sample collection and preparation procedures are labor-intensive and may introduce bias due to spatial heterogeneity in large compost piles or windrows^[39]. Wet chemistry methods for nutrient determination require chemical reagents, specialized equipment, and trained personnel, resulting in analysis costs ranging from \$50 to several hundred dollars per sample^[40]. Turnaround times of several days to weeks delay decision-making for process optimization or quality-based pricing. Most critically, destructive sampling prevents continuous monitoring and provides only point measurements rather than comprehensive spatial quality mapping. These limitations create strong demand for rapid, non-destructive, and cost-effective quality assessment technologies that can support both large-scale commercial operations and precision agriculture applications.

3. Hyperspectral Imaging for Compost Analysis

3.1. Principles of Hyperspectral Imaging

Hyperspectral imaging combines the spatial information of conventional imaging with the spectral discrimination capability of spectroscopy, acquiring a complete spectrum at each pixel location to create three-dimensional data cubes with two spatial dimensions and one spectral dimension. Unlike multispectral imaging systems that capture information in a few discrete broad bands, hyperspectral sensors record reflectance or transmittance across hundreds of contiguous narrow bands (typically 5–10 nm bandwidth) spanning visible (VIS, 400–700 nm), near-infrared (NIR, 700–1000 nm), and shortwave infrared (SWIR, 1000–2500 nm) regions.

The fundamental principle underlying hyperspectral analysis of organic materials relies on the interaction between electromagnetic radiation and molecular vibrations and electronic transitions. Organic molecules containing C-H, O-H, N-H, C-O, C-N, and other functional groups exhibit characteristic absorption features at specific wavelengths due to overtones and combinations of fundamental vibrational modes occurring in the mid-infrared region. Water content strongly influences spectra through broad O-H absorption bands centered around 1450 nm and 1940 nm, while organic carbon compounds show absorption features near 1200 nm, 1730 nm, and 2200–2300 nm. Nitrogen-containing compounds, particularly proteins and amino acids, exhibit absorption features around 1510 nm, 1980 nm, and 2180 nm.

3.2. Spectral Characteristics of Compost Materials

Compost materials display complex spectral signatures reflecting their heterogeneous composition and transformation during decomposition. Fresh organic feedstocks exhibit distinct spectral features associated with cellulose, hemicellulose, lignin, proteins, and water content, with prominent absorption bands in the NIR and SWIR regions. As composting progresses, spectral profiles evolve due to the breakdown of labile organic compounds, formation

of humic substances, changes in moisture content, and modification of surface properties.

Mature compost typically shows increased absorption in the visible region due to darker coloration from humic acid accumulation, along with modified NIR and SWIR features reflecting reduced cellulose and protein content and increased recalcitrant aromatic structures. The ratio of absorption intensities at specific wavelength pairs has been correlated with maturity indices and C/N ratio. Moisture content exerts strong influence on overall spectral shape and intensity, necessitating either moisture correction algorithms or measurement under standardized moisture conditions.

3.3. Imaging Systems and Acquisition Protocols

Hyperspectral imaging systems for compost analysis can be categorized into laboratory-based benchtop systems and portable or field-deployable configurations. Laboratory systems typically employ pushbroom line-scanning designs where the sample moves on a conveyor belt beneath a stationary imaging spectrograph that disperses light from a linear field of view onto a two-dimensional detector array. These systems offer high spectral and spatial resolution, controlled illumination conditions using halogen or LED lamps, and precise calibration capabilities.

Field-deployable systems prioritize portability and robustness, often utilizing snapshot spectral imaging or handheld point spectrometers with spatial scanning mechanisms. Recent developments in compact, cooled InGaAs detectors and improved miniaturization have enabled SWIR hyperspectral cameras suitable for outdoor environments and integration with mobile platforms including conveyor systems at compost facilities.

Acquisition protocols must address several critical factors: standardized sample presentation to minimize surface roughness effects, appropriate illumination geometry to reduce specular reflection from moist surfaces, calibration using white reference materials and dark current measurements, and optimal spatial resolution matching the characteristic particle size of compost samples. Typical imaging configurations employ spatial resolutions of 0.5–2 mm per pixel for laboratory measurements and 5–10 mm for industrial implementations.

3.4. Laboratory and Field-Scale Implementations

Laboratory applications of hyperspectral imaging for compost research have demonstrated successful quantification of organic carbon, total nitrogen, C/N ratio, moisture content, and ash content with coefficient of determination (R^2) values typically exceeding 0.80–0.90 when using appropriate calibration models. Studies have examined compost derived from various feedstocks including agricultural residues, municipal solid waste, sewage sludge, and animal manures, establishing the generalizability of the hyperspectral approach across different compost types.

Field-scale implementations have been developed for inline monitoring at commercial composting facilities, where hyperspectral cameras installed above conveyor belts capture spectral images of compost during screening and packaging operations. These systems enable continuous quality assessment, automated sorting based on nutrient content or maturity level, and generation of spatial quality maps that identify heterogeneous regions within batches. Integration with facility management software allows real-time quality control and documentation for certification programs.

4. Machine Learning and Automated Analysis

4.1. Spectral Preprocessing and Feature Extraction

Raw hyperspectral data requires preprocessing to remove systematic noise, correct for illumination variations, and enhance chemically relevant information. Standard preprocessing techniques include Standard Normal Variate (SNV) transformation to remove multiplicative scatter effects, Savitzky-Golay smoothing and derivative calculations to emphasize absorption features and remove baseline drift, and multiplicative scatter correction (MSC) to normalize spectra to a common baseline. First and second derivative spectra are particularly effective for compost analysis as they resolve overlapping absorption bands and reduce the influence of particle size and surface characteristics.

Dimensionality reduction and feature extraction techniques address the high-dimensional nature of hyperspectral data, where hundreds of spectral bands create multicollinearity challenges and increase computational requirements. Principal Component Analysis (PCA) transforms correlated spectral variables into uncorrelated principal components that capture maximum variance in the data, typically retaining 95–99% of spectral information in 5–15 components. Wavelength selection algorithms including Competitive Adaptive Reweighted Sampling (CARS), Successive Projections Algorithm (SPA), and regression coefficient analysis identify the most informative spectral bands for specific quality parameters, reducing model complexity while maintaining prediction accuracy.

4.2. Regression and Classification Models

Partial Least Squares Regression (PLSR) represents the most widely adopted machine learning approach for hyperspectral prediction of continuous compost quality parameters such as nutrient concentrations and moisture content. PLSR handles multicollinearity effectively by decomposing spectral data into latent variables that maximize covariance with the response variable, typically achieving root mean square error of prediction (RMSEP) values of 0.2–0.5% for nitrogen content and 2–5% for organic carbon content. Support Vector Machine Regression (SVR) provides nonlinear modeling capability through kernel functions, demonstrating superior performance for complex relationships between spectra and quality parameters particularly when combined with optimized hyperparameters.

Classification models for categorical quality assessments, such as maturity grading into classes (immature, semi-mature, mature), employ algorithms including Linear Discriminant Analysis (LDA), Support Vector Classification (SVC), Random Forest (RF), and k-Nearest Neighbors (k-NN). Random Forest classifiers, which construct ensembles of decision trees trained on bootstrap samples with random feature subsets, have achieved classification accuracies exceeding 90–95% for compost maturity categorization. These models inherently provide variable importance rankings that identify the most discriminative wavelength regions for classification tasks.

4.3. Deep Learning for Spatial-Spectral Analysis

Convolutional Neural Networks (CNNs) and their variants have emerged as powerful tools for automated feature extraction and quality prediction from hyperspectral images [79]. Unlike conventional machine learning approaches that require manual feature engineering, deep learning

architectures automatically learn hierarchical representations from raw spectral data through multiple layers of convolution, pooling, and nonlinear activation functions. One-dimensional CNNs applied to spectral signatures have demonstrated competitive or superior performance compared to traditional chemometric methods for nutrient prediction. Hybrid spatial-spectral CNN architectures simultaneously process spectral information and spatial context from neighboring pixels, enabling detection of quality variations and contamination spots within compost samples. Recurrent neural networks, particularly Long Short-Term Memory (LSTM) networks, can model sequential dependencies in spectral data and have been applied to time-series monitoring of composting processes using sequential hyperspectral measurements. Despite promising results, deep learning approaches require large training datasets and significant computational resources, presenting challenges for applications with limited sample availability.

4.4. Automated Quality Grading Systems

Integration of machine learning models into automated decision support systems enables real-time compost quality assessment without human intervention. These systems typically comprise several modules: hyperspectral image acquisition and calibration, preprocessing and segmentation to separate compost from background, pixel-wise or region-wise spectral feature extraction, application of trained prediction models to estimate quality parameters, and generation of quality maps and grading decisions based on predefined acceptance criteria.

Advanced implementations incorporate uncertainty quantification through prediction intervals or ensemble modeling, providing confidence estimates alongside quality predictions to support risk-informed decision-making. Automated alerts can be triggered when quality parameters fall outside specified ranges, enabling rapid corrective actions during composting or preventing shipment of substandard products. Cloud-based platforms facilitate remote monitoring across multiple composting facilities and enable continuous model improvement through data accumulation and periodic recalibration.

5. Agricultural and Environmental Applications

5.1. Nutrient-Based Compost Application Planning

Precision agriculture strategies require accurate nutrient information to optimize organic fertilizer application rates and timing, minimizing excess application that wastes resources and contributes to environmental pollution while preventing under-application that limits crop productivity. Hyperspectral imaging-based nutrient characterization enables site-specific compost management by providing rapid, spatially resolved nutrient content maps that inform variable rate application systems. When compost quality data is integrated with soil nutrient status from precision soil sampling and crop nutrient demand models, farmers can develop prescription maps for variable rate spreading equipment, applying appropriate amounts based on actual nutrient content rather than assumed average values.

This approach offers particular value for compost derived from heterogeneous feedstocks where nutrient composition varies substantially between batches and even within individual batches. Real-time quality assessment during compost loading onto spreading equipment could enable dynamic adjustment of application rates to compensate for

nutrient variability, achieving uniform nutrient distribution despite variable compost quality. Economic analyses suggest that improved application efficiency can reduce compost usage by 10–25% while maintaining equivalent crop yields, generating significant cost savings for large-scale organic farming operations.

5.2. Process Monitoring During Composting

Application of hyperspectral imaging for temporal monitoring throughout composting operations provides insights into decomposition kinetics, maturity progression, and process optimization opportunities. Sequential spectral measurements at different stages of the composting cycle reveal characteristic spectral evolution patterns associated with organic matter transformation, enabling prediction of maturity achievement time and identification of process anomalies such as insufficient aeration or moisture imbalance.

Automated monitoring systems can track key process indicators including temperature, moisture content, and spectral indices correlating with microbial activity, generating alerts when parameters deviate from optimal ranges. This information supports adaptive process management where aeration rates, moisture addition, or turning frequency are adjusted based on actual compost condition rather than fixed schedules. Studies have demonstrated that spectral monitoring-guided process control can reduce composting time by 15–30% while improving final product quality and consistency.

5.3. Quality Assurance for Commercial Compost

Commercial compost producers face increasing regulatory requirements and customer expectations for quality documentation and certification. Traditional quality assurance programs relying on infrequent laboratory sampling fail to detect batch-to-batch variations and provide limited traceability. Hyperspectral imaging systems integrated into production lines enable 100% quality inspection, documenting nutrient content, maturity status, and potential contamination for every batch or even subdividing large batches into quality zones.

This comprehensive quality data supports premium pricing for high-quality compost, facilitates compliance with organic certification standards, and builds customer confidence through transparent quality reporting. Advanced applications include automated blending of compost batches to achieve target nutrient specifications and contamination screening to detect plastic fragments, stones, or other foreign materials based on spectral differences from organic material.

5.4. Environmental and Economic Benefits

Adoption of intelligent compost quality monitoring contributes to multiple environmental and economic objectives aligned with sustainable agriculture principles. Improved nutrient management reduces excess application that would otherwise contribute to nitrate leaching into groundwater, phosphorus runoff to surface waters causing eutrophication, and greenhouse gas emissions from nitrogen transformations in soil. Enhanced compost quality assessment supports waste diversion from landfills by enabling utilization of variable-quality feedstocks through targeted processing and appropriate end-use matching. Economic benefits extend beyond operational efficiency improvements to include market advantages from certified

quality products, reduced liability risks associated with contaminated or immature compost application, and enhanced reputation for environmental stewardship. Life cycle assessments indicate that technology investments in hyperspectral imaging systems are typically recovered within 2–5 years through a combination of reduced laboratory costs, decreased compost overapplication, quality-based premium pricing, and waste processing credits.

6. Challenges and Future Perspectives

6.1. High Dimensionality of Hyperspectral Data

The inherent high dimensionality of hyperspectral images, with hundreds of spectral bands and potentially millions of pixels per image, creates computational challenges for data processing, storage, and real-time analysis. While dimensionality reduction techniques mitigate some concerns, they require careful optimization to preserve chemically relevant information while removing redundant data. Development of efficient compression algorithms and data reduction strategies specific to compost spectral characteristics represents an important research direction.

Edge computing approaches that perform initial processing and feature extraction directly on imaging hardware before data transmission can reduce bandwidth requirements and enable faster response times for automated systems. However, implementation of complex machine learning models on resource-constrained edge devices necessitates model optimization techniques including quantization, pruning, and knowledge distillation.

6.2. Model Robustness and Transferability

Machine learning models trained on data from specific compost types, feedstocks, or production facilities often exhibit reduced accuracy when applied to new conditions not represented in the training set. This transferability challenge limits the practical deployment of universal models and necessitates site-specific calibration, increasing implementation costs and complexity. Sources of model bias include variations in composting processes, feedstock composition, spectral instrument characteristics, and environmental conditions during measurement.

Transfer learning approaches that leverage pre-trained models and adapt them to new contexts using limited local calibration samples show promise for improving transferability. Domain adaptation techniques from computer vision, which minimize distribution differences between training and target domains, are beginning to be explored for hyperspectral applications. Establishment of standardized reference compost samples and collaborative databases containing diverse spectral datasets would facilitate development of more robust models.

6.3. System Cost and Operational Complexity

Current hyperspectral imaging systems remain relatively expensive, with laboratory-grade instruments costing \$50,000–\$150,000 and field-deployable systems ranging from \$20,000–\$80,000 depending on spectral range and specifications. These capital costs, combined with requirements for technical expertise in system operation, calibration, and data analysis, present barriers to adoption particularly for small and medium-sized composting operations.

Technology development efforts focused on sensor miniaturization, utilization of lower-cost detector

technologies, and simplified turnkey systems with integrated analysis software are essential for broader market penetration. Multispectral imaging systems with fewer carefully selected bands optimized for key compost parameters offer a potential cost-effective alternative, albeit with reduced information content compared to full hyperspectral acquisition. Equipment sharing models, third-party testing services, and mobile quality assessment units that serve multiple facilities represent alternative implementation pathways that distribute costs across multiple users.

6.4. Future Integration with Smart Agriculture Platforms

The convergence of hyperspectral compost monitoring with broader digital agriculture ecosystems presents exciting opportunities for holistic nutrient management. Integration with precision agriculture platforms that combine soil

sensing, crop monitoring, yield mapping, and weather data enables comprehensive nutrient budgeting that considers all nutrient sources and sinks within farming systems. Blockchain-based traceability systems could incorporate hyperspectral quality data to create verifiable records of compost characteristics from production through field application.

Artificial intelligence agents that autonomously optimize composting processes, predict quality outcomes, recommend application strategies, and adapt to changing conditions through continuous learning represent the next frontier in intelligent compost management. Development of industry standards for data formats, communication protocols, and quality metrics will facilitate interoperability between different technology platforms and enable widespread data sharing to accelerate innovation.

7. Figures




Fig 1: Workflow of smart compost quality monitoring using hyperspectral imaging and machine learning




Fig 2: Representative hyperspectral signatures of compost at different maturity stages




Fig 3: Integrated decision-support framework for compost quality-based nutrient management

8. Tables

Table 1: Compost quality parameters and their agronomic significance

Quality Parameter	Typical Range	Agronomic Significance	Assessment Method
Organic matter content	25–65% (dry basis)	Soil structure improvement, carbon sequestration, microbial habitat	Loss on ignition, combustion analysis
Total nitrogen	0.5–3.5% (dry basis)	Crop nutrition, mineralization dynamics	Kjeldahl digestion, combustion analysis
C/N ratio	10–30	Nitrogen availability vs. immobilization	Calculated from C and N content
Moisture content	30–60% (wet basis)	Storage stability, handling properties, microbial activity	Gravimetric drying at 105°C
pH	6.0–8.5	Nutrient availability, soil acidity buffering	Potentiometric measurement
Available phosphorus	0.2–1.5% P ₂ O ₅	Crop nutrition, root development	Extractable P determination
Exchangeable potassium	0.5–2.0% K ₂ O	Crop nutrition, plant stress tolerance	Extractable K determination
Electrical conductivity	2–8 dS/m	Salinity, potential for salt stress	Conductivity measurement in extract
Maturity indices	Variable	Phytotoxicity risk, stability	Germination index, respiration rate
Heavy metals	Regulated limits	Environmental safety, food chain contamination	Atomic absorption, ICP-MS

Table 2: Hyperspectral wavelength regions associated with compost constituents

Wavelength Range (nm)	Associated Molecular Vibrations	Compost Constituents	Relevance to Quality Assessment
400–700 (VIS)	Electronic transitions, π -bonding	Humic acids, chromophores, minerals	Maturity indication through color, contamination detection
900–1100	2nd overtone C-H stretch	Cellulose, hemicellulose, lipids	Labile organic matter content
1200–1250	2nd overtone C-H stretch, C-H combination	Organic carbon compounds	Total organic carbon estimation
1400–1500	1st overtone O-H stretch	Water, hydroxyl groups	Moisture content determination
1450–1550	1st overtone N-H stretch, O-H stretch	Proteins, amino acids, water	Nitrogen content prediction
1680–1800	1st overtone C-H stretch	Cellulose, organic compounds	Structural carbohydrate content
1900–2000	O-H combination, H ₂ O bend + stretch	Water	Moisture quantification
2100–2200	C-O stretch, C-N combination	Proteins, cellulose	Nitrogen and carbon estimation
2200–2400	C-H combination, C-O, O-H combination	Lignin, cellulose, hemicellulose	Recalcitrant organic matter, maturity

Table 3: Machine learning models used for compost quality prediction

Model Type	Algorithm Examples	Typical Application	Performance Metrics	Advantages	Limitations
Linear regression	Multiple Linear Regression (MLR), Principal Component Regression (PCR)	Nutrient concentration prediction	$R^2 = 0.70-0.85$, RMSE moderate	Simple, interpretable, low computational cost	Limited for nonlinear relationships, multicollinearity issues
Latent variable regression	Partial Least Squares Regression (PLSR)	Nutrient and moisture content quantification	$R^2 = 0.80-0.95$, RMSE low	Handles multicollinearity, effective for spectral data	Requires careful component number selection
Support vector machines	SVR with RBF/polynomial kernels, SVC	Nonlinear nutrient prediction, maturity classification	$R^2 = 0.85-0.95$, Accuracy 90–95%	Effective for high-dimensional data, robust to overfitting	Computationally intensive, sensitive to hyperparameters
Tree-based ensembles	Random Forest (RF), Gradient Boosting, XGBoost	Classification and regression, variable selection	$R^2 = 0.82-0.94$, Accuracy 88–95%	Handles nonlinearity, provides feature importance, robust	Less interpretable, prone to overfitting with small datasets
Neural networks	Multilayer Perceptron (MLP), 1D-CNN, LSTM	Complex pattern recognition, spatial-spectral analysis	$R^2 = 0.85-0.96$, Accuracy 91–97%	Automatic feature learning, captures complex relationships	Requires large datasets, computationally expensive, black-box nature
Discriminant analysis	Linear/Quadratic Discriminant Analysis (LDA/QDA)	Maturity classification, quality grading	Accuracy 85–92%	Probabilistic classification, computationally efficient	Assumes specific data distributions

Table 4: Advantages and limitations of hyperspectral imaging-based compost monitoring

Aspect	Advantages	Limitations
Measurement speed	Rapid analysis (seconds to minutes per sample), enables high-throughput screening and real-time monitoring	Initial system setup and calibration time-consuming
Sample preparation	Non-destructive, no chemical reagents required, minimal sample handling	Surface measurement only, may not represent bulk composition for heterogeneous materials
Spatial coverage	Complete spatial mapping of quality variability within samples or batches, identifies heterogeneous zones	Large data volumes require significant storage and processing capacity
Multiple parameters	Simultaneous prediction of multiple quality indicators from single measurement	Accuracy varies between parameters, some constituents poorly predicted
Operational costs	Reduced laboratory costs after initial investment, lower consumable expenses	High capital cost for instrumentation (\$20,000–\$150,000)
Automation potential	Fully automatable for inline quality control, minimal operator intervention needed	Requires technical expertise for system maintenance and model development
Environmental impact	No hazardous waste generation, supports sustainable practices	Equipment manufacturing and energy consumption considerations
Data richness	Comprehensive spectral information enables exploratory analysis and model improvement	Complex data structures require advanced analytical skills
Calibration transferability	Models can potentially be shared across similar systems	Often requires site-specific recalibration, limiting universality
Real-time feedback	Immediate quality information supports adaptive decision-making	Model prediction uncertainty requires appropriate interpretation

9. Conclusion

Hyperspectral imaging coupled with machine learning represents a transformative technological advancement for compost quality monitoring, offering rapid, non-destructive, and spatially comprehensive assessment capabilities that overcome fundamental limitations of conventional analytical methods. The technology enables automated quantification of critical quality parameters including nutrient concentrations, moisture content, and maturity indices with accuracy approaching or matching laboratory reference methods. Integration of these intelligent monitoring systems into composting operations and precision agriculture workflows provides substantial benefits including optimized nutrient management, enhanced process control, improved product quality assurance, and measurable environmental and economic advantages.

Successful implementations across laboratory and commercial scales have demonstrated technical feasibility and practical value, particularly for applications requiring high-throughput analysis, continuous monitoring, or spatial

quality mapping. Machine learning algorithms, ranging from traditional chemometric approaches to advanced deep learning architectures, effectively extract quality information from complex hyperspectral data and enable automated decision support with minimal human intervention.

Despite significant progress, important challenges remain that must be addressed to realize the full potential of smart compost monitoring technologies. Research priorities include improving model robustness and transferability across diverse compost types and production systems, reducing system costs through sensor innovation and streamlined designs, developing standardized protocols and reference materials to facilitate model sharing and validation, and creating seamless integration pathways with existing agricultural management platforms.

Future developments in artificial intelligence, Internet of Things connectivity, and edge computing will enable increasingly sophisticated autonomous monitoring systems that continuously learn and adapt to changing conditions. As these technologies mature and costs decline, hyperspectral

imaging-based compost quality assessment is positioned to become a standard tool in sustainable agriculture, supporting the transition toward circular nutrient economies and precision management of organic resources.

10. References

- Nayak A, Bhushan B. An overview of the recent trends on the waste valorization techniques for food wastes. *Journal of Environmental Management*. 2019;233:352–370.
- Pandey PK, Vaddella V, Cao W, Biswas S, Chiu C, Hunter S. In-vessel composting system for converting food and green wastes into pathogen-free soil amendment for sustainable agriculture. *Journal of Cleaner Production*. 2016;139:407–415.
- Gómez-Brandón M, Lores M, Domínguez J. A new guaranteed low-cost technology for the automated determination of manure chemical properties. *Bioresource Technology*. 2013;123:214–219.
- Bernal MP, Alburquerque JA, Moral R. Composting of animal manures and chemical criteria for compost maturity assessment: A review. *Bioresource Technology*. 2009;100(17):5444–5453.
- Hargreaves JC, Adl MS, Warman PR. A review of the use of composted municipal solid waste in agriculture. *Agriculture, Ecosystems and Environment*. 2008;123(1):1–14.
- Thompson W, Legee P, Millner P, Watson M. *Test Methods for the Examination of Composting and Compost*. Bethesda (MD): US Composting Council; 2002.
- Zmora-Nahum S, Markovitch O, Tarchitzky J, Chen Y. Dissolved organic carbon (DOC) as a parameter of compost maturity. *Soil Biology and Biochemistry*. 2005;37(12):2109–2116.
- Lasaridi K, Protopapa I, Kotsou M, Pilidis G, Manios T, Kyriacou A. Quality assessment of composts in the Greek market: The need for standards and quality assurance. *Journal of Environmental Management*. 2006;80(1):58–65.
- Gómez-Brandón M, Lazcano C, Lores M, Domínguez J. Short-term stabilization of grape marc through earthworms. *Journal of Hazardous Materials*. 2011;187(1–3):291–295.
- ElMasry G, Nakauchi S. Image analysis operations applied to hyperspectral images for non-invasive sensing of food quality: A comprehensive review. *Biosystems Engineering*. 2016;142:53–82.
- Yao H, Lewis D. Spectral preprocessing and calibration techniques. In: *Hyperspectral Imaging for Food Quality Analysis and Control*. London: Academic Press; 2010. p. 45–78.
- Lu G, Fei B. Medical hyperspectral imaging: A review. *Journal of Biomedical Optics*. 2014;19(1):010901.
- Gowen AA, O'Donnell CP, Cullen PJ, Downey G, Frias JM. Hyperspectral imaging—an emerging process analytical tool for food quality and safety control. *Trends in Food Science and Technology*. 2007;18(12):590–598.
- Manley M. Near-infrared spectroscopy and hyperspectral imaging: Non-destructive analysis of biological materials. *Chemical Society Reviews*. 2014;43(24):8200–8214.
- Rossel RAV, Behrens T. Using data mining to model and interpret soil diffuse reflectance spectra. *Geoderma*. 2010;158(1–2):46–54.
- Jia S, Liang G, Zhou X, Xu M, Yu X, Tang Z. Hyperspectral imaging analysis for the classification of soil types and the determination of soil total nitrogen. *Sensors*. 2017;17(10):2252.
- Ng W, Minasny B, Montazerolghaem M, Padian J, Ferguson R, Bailey S, et al. Convolutional neural network for simultaneous prediction of several soil properties using visible/near-infrared, mid-infrared, and combined spectra. *Geoderma*. 2019;352:251–267.
- Zhang Y, Biswas A, Ji W, Li H, Qin Q, Liu F. Integrating spectral and textural information for identifying the tasseling date of summer maize using UAV-based RGB images. *International Journal of Applied Earth Observation and Geoinformation*. 2021;102:102435.
- Chen S, Xu D, Li S, Ji W, Yang M, Zhou Y, et al. Monitoring soil organic carbon in alpine soils using in situ visible–near infrared spectroscopy and a multilayer perceptron. *Land Degradation and Development*. 2020;31(8):1026–1038.
- Zmora-Nahum S, Hadar Y, Chen Y. Physico-chemical properties of commercial composts varying in their source materials and country of origin. *Soil Biology and Biochemistry*. 2007;39(6):1263–1276.
- Jiménez EI, García VP. Evaluation of city refuse compost maturity: A review. *Biological Wastes*. 1989;27(2):115–142.
- Haug RT. *The Practical Handbook of Compost Engineering*. Boca Raton (FL): Lewis Publishers; 1993.
- Hue NV, Liu J. Predicting compost stability. *Compost Science and Utilization*. 1995;3(2):8–15.
- Benito M, Masaguer A, De Antonio R, Moliner A. Use of pruning waste compost as a component in soilless growing media. *Bioresource Technology*. 2005;96(5):597–603.
- Iglesias-Jiménez E, Pérez-García V. Determination of maturity indices for city refuse composts. *Agriculture, Ecosystems and Environment*. 1992;38(4):331–343.
- Bernal MP, Sánchez-Monedero MA, Paredes C, Roig A. Carbon mineralization from organic wastes at different composting stages during their incubation with soil. *Agriculture, Ecosystems and Environment*. 1998;69(3):175–189.
- Cooperband LR, Stone AG, Fryda MR, Ravet JL. Relating compost measures of stability and maturity to plant growth. *Compost Science and Utilization*. 2003;11(2):113–124.
- Komilis DP, Ham RK. The effect of lignin and sugars on the aerobic decomposition of solid wastes. *Waste Management*. 2003;23(5):419–423.
- Barrena R, d'Imporzano G, Ponsá S, Gea T, Artola A, Vázquez F, et al. In search of a reliable technique for the determination of the biological stability of organic matter in mechanically treated wastes. *Journal of Hazardous Materials*. 2008;162(2–3):1065–1072.
- Zucconi F, Pera A, Forte M, De Bertoldi M. Evaluating toxicity of immature compost. *BioCycle*. 1981;22(2):54–57.
- Wu L, Ma LQ, Martinez GA. Comparison of methods for evaluating stability and maturity of biosolids compost. *Journal of Environmental Quality*. 2000;29(2):424–429.
- Golueke CG. Epidemiological aspects of sludge handling and management—Part III. *BioCycle*.

- 1983;24(3):49–52.
33. Woods End Research Laboratory. Solvita Compost Maturity Index: Field Guide and Laboratory Procedures. Mt Vernon (ME): Woods End Research Laboratory; 2001.
 34. Iannotti DA, Pang T, Toth BL, Elwell DL, Keener HM, Hoitink HAJ. A quantitative respirometric method for monitoring compost stability. *Compost Science and Utilization*. 1993;1(3):52–65.
 35. Raviv M, Medina S, Krasnovsky A, Ziadna H. Organic matter and nitrogen conservation in manure compost for organic agriculture. *Compost Science and Utilization*. 2004;12(1):6–10.
 36. Liang C, Das KC, McClendon RW. The influence of temperature and moisture content regimes on the aerobic microbial activity of a biosolids composting blend. *Bioresource Technology*. 2003;86(2):131–137.
 37. Albrecht R, Périsol C, Ruauzel F, Le Petit J, Terroma M. Functional changes in culturable microbial communities during a co-composting process: Carbon source utilization and co-metabolism. *Waste Management*. 2010;30(5):764–770.
 38. Inbar Y, Chen Y, Hadar Y. Recycling of cattle manure: The composting process and characterization of maturity. *Journal of Environmental Quality*. 1993;22(4):857–863.
 39. Said-Pullicino D, Erriquens FG, Gigliotti G. Changes in the chemical characteristics of water-extractable organic matter during composting and their influence on compost stability and maturity. *Bioresource Technology*. 2007;98(9):1822–1831.
 40. Paredes C, Roig A, Bernal MP, Sánchez-Monedero MA, Cegarra J. Evolution of organic matter and nitrogen during co-composting of olive mill wastewater with solid organic wastes. *Biology and Fertility of Soils*. 2000;32(3):222–227.